

















TK-200/450

LED Daylight Soft Panel Light



1. Ultra-efficient, bright, daylight illumination
2. Flicker free, fully dimmable between 0 and 100%
3. Built-in 11 customisable practical effects
4. Support both wired and wireless control via NANLINK APP, DMX/RDM, Remote Control and Lumenradio CRMX

| | | | | | |
|---|---|---|---|---|---|
|  |  |  |  |  | |
| INT LOOP | FLASH | PULSE | STORM | TV | |
|  |  |  |  |  |  |
| PAPARAZZI | CANDLE/FIRE | BAD BULB | FIREWORK | EXPLOSION | WELDING |
|  |  |  |  |  | |
| On-board | DMX/RDM | Remote Control | NANLINK APP | Lumenradio | |



BRIGHTER AND STRONGER, DEDICATE TO PROFESSIONAL

TK-200/450 is an exceptional high power and compact LED panel with uniform lighting in the market. Power reach up to 240W and 455W and able to produce stronger output and meet the illumination requirements in the large scene.

Includes:

TK-200/450 × 1, Barndoor × 1,
Power Supply × 1, Power Cable × 1,
Yoke × 1, DMX Reference Guide × 1,
User Manual × 1,
Connection cable x 1 (Only for TK-450)

Multiple Accessories, More Applications



EC-TK200/450
Eggcrate

CC-TK200/450-2-FT
Flight case for Dual TK-200/450

HC-TK200/450
Honeycomb Grid

AS-FC-TK200/450
Fixture Cover

| TK Technical Data | | |
|-------------------------|--|--|
| Model | TK-200 | TK-450 |
| Rated Power | 240W | 455W |
| Input Voltage/Current | DC 24V/10.4A Max, AC 100-240V 50/60Hz | DC 48V/10A Max, AC 100-240V 50/60Hz |
| Beam Angle | 120° | |
| CRI | 96 | |
| TLCI | 98 | |
| CCT | 5600K | |
| Dimming | 0-100% | |
| Control | On-board, Remote Control, NANLINK APP, DMX/RDM, Lumenradio CRMX | |
| Effects | INT Loop, Flash, Pulse, Storm, TV, Paparazzi, Candle/Fire, Bad Bulb, Firework, Explosion and Welding | |
| Housing | Aluminium | |
| Mounting | Yoke | |
| Cooling | Passive air cooling | |
| Product Size | Light fixture (with yoke): 890×85×540mm/35.04×3.35×21.3" | Light fixture (with yoke): 1340×85×540mm/52.76×3.35×21.3" |
| Product Weight | Light fixture+Yoke+Barndoor: 8.14kg/17.95lb | Light fixture+Yoke+Barndoor: 11.84kg/26lb |
| Illumination (lux / fc) | | |
| Model | TK-200 | TK-450 |
| Distance | 5600K | |
| 1M | 6888 lux / 640 fc | 12480 lux / 1159 fc |
| 3M | 901 lux / 84 fc | 1776 lux / 165 fc |
| 5M | 374 lux / 35 fc | 736 lux / 68 fc |
| 7M | 208 lux / 19 fc | 405 lux / 38 fc |